

Model 2015 NiMH

45 W max out • 230 VAC input

- AC/DC Switch mode fast charger
- 120 VAC model available
- Computer Programmable Microprocessor (CPM)

CPM offers the following charge detection options (one or more):

dV, dT/dt, 0 dV, Timer, Safety timer, dV threshold,

Temperature gradient adjustment

[Link to CPM spec sheet](#)

- Custom specifications on request:

Charging parameters, connectors, cords, logo print, housing/open frame/IP rating and certificates. For more information: [custom design info sheet](#)

Notes:

Plug-in unit

Exchangeable DC plugs available



Available versions

- 3-6 cells / 3,5A
- 4-8 cells / 2,8A
- 5-10 cells / 2,2A
- 6-12 cells / 1,8A
- 10-20 cells / 1,2A

DATE 21.01.11

SPECIFICATIONS FOR TYPE 2015:	3-6 cells	4-8 cells	5-10 cells	6-12 cells	10-20 cells
Input voltage	190-265VAC, 50-60Hz	190-265VAC, 50-60Hz	190-265VAC, 50-60Hz	190-265VAC, 50-60Hz	190-265VAC, 50-60Hz
No-load voltage	12.8V \pm 0.7V	16.5V \pm 1V	21V \pm 1.2V	24.7V \pm 1.5V	41V \pm 2V
Max. output power	40W	40W	40W	40W	45W
Min. output voltage for - Δ V detection	3.7V (min 3 cells x min 1.25V pr. cell)	5.0V (min 4 cells x min 1.25V pr. cell)	6.2V (min 5 cells x min 1.25V pr. cell)	7.5V (min 6 cells x min 1.25V pr. cell)	12.5V (min 20 cells x min 1.25V pr. cell)
Max. output voltage for - Δ V detection	10.8V (max 6 cells x max 1.8V pr. cell)	14.4V (max 8 cells x max 1.8V pr. cell)	18V (max 10 cells x max 1.8V pr. cell)	21.6V (max 12 cells x max 1.8V pr. cell)	36V (max 20 cells x max 1.8V pr. cell)
- Δ V sensitivity mV/cell or percent	12mV/0.7% at 3 cells. 10mV/0.6% at 6 cells.	8mV / 0.5% for 4-8 cells	8mV / 0.5% for 5-10 cells	8mV / 0.5% for 6-12 cells	8mV / 0.5% for 10-20 cells
Fast charge current	3.5A \pm 250mA	2.8A \pm 200mA	2.2A \pm 150mA	1.8A \pm 150mA	1.2A \pm 100mA
Top off charge	480mA \pm 100mA (duration 1h after -dV detection)	400mA \pm 80mA (duration 1h after -dV detection)	330mA \pm 70mA (duration 1h after -dV detection)	270mA \pm 60mA (duration 1h after -dV detection)	160mA \pm 50mA (duration 1h after -dV detection)
Trickle charge current	150mA \pm 70mA (continuously)	150mA \pm 70mA (continuously)	100mA \pm 50mA (continuously)	100mA \pm 50mA (continuously)	50mA \pm 25mA (continuously)
Leakage current from battery with mains switch off	< 1mA	< 1mA	< 1mA	< 1mA	< 1mA
Start timer	3 min, no - Δ V detection in this period	3 min, no - Δ V detection in this period	3 min, no - Δ V detection in this period	3 min, no - Δ V detection in this period	3 min, no - Δ V detection in this period
Top-off timer	1hour	1hour	1hour	1hour	1hour
Safety timer	2 h	2 h	2 h	2 h	2 h
	The charger switch to trickle charge if no - Δ V is detected before the safety timer has run out.				
Switch frequency	40kHz.				
Temperature range	-20 to +40°C (these values are only for the charger, not for the batteries).				
Charge control	- Δ V principle. Fast charging stops when the voltage has dropped 0.5% below its maximum recorded level.				
Voltage changes during charging	- Δ V detection is disabled if the voltage changes quickly. This to avoid false - Δ V if an external load kicks in during charging.				
Battery analyzing	Max. 20 sec after mains connection / battery connection (yellow LED).				
Efficiency	Appr. 78%.				
Fuses	Fusible resistor at input. Polyswitch fuse at the output protects the unit against wrong polarity.				
Insulation class	Class II.				
Electrical safety	EN 60601-1, EN 60950, EN 60335-2-29.				
EMC-standards	EN 61000-6-3, EN 50081-1, EN 61000-6-1, EN 50082-1, EN 60601-1-2.				

SPECIFICATIONS FOR TYPE 2015:	3-6 cells	4-8 cells	5-10 cells	6-12 cells	10-20 cells
Insulation voltage (prim-sec)	4000V AC / 5700V DC.				
Mains connection	Plug-in europlug (UK, AU and US-plug also available)				
Output terminals	Secondary cable with exchangeable plugs.				
LED-indication	Initialization/no batt.: Yellow Fast charge: Orange Top off charge: Green with short yellow flashes Trickle charge: Green Battery voltage low: Red-Green flashing (error mode)				
Resetting	A new charging cycle starts by reconnecting a battery at the output, or by disconnecting and connecting the mains voltage.				
IP-grade	IP 20.				
Dimensions	L100 × W63 × H47 (without plug).				
Weight	220g.				
Other	Possible options on request: +dT/dt, 0dV and timer charge. The charger may be both software and hardware-programmable.				

Technical drawing



